



ARDEX E 90

Synthetic resin admix

- Production of a highly deformable, water-repellent adhesive bed



Area of application

Indoor and exterior use.

Synthetic resin admix for X7G – The formula for success / Ardex X 77 / Ardex X 77 W / Ardex X 77 S / Ardex X 90 / Ardex N 23 W NEW / Ardex X 78

In combination with X7G – THE FORMULA FOR SUCCESS:

- Creating a highly deformable, water-repellent adhesive bed
- Laying porcelain tiles on balconies and terraces
- Installing ceramic cladding on facades
- Installing and laying tiles on concrete and masonry substrates that are still shrinking (at least 3 months old)
- Laying on existing tiles and slab coverings

In combination with ARDEX X 77 W / X 77 S:

- Creating a highly deformable, water-repellent adhesive bed
- Installing and laying of porcelain tiles
- Installing and laying tiles on concrete and masonry substrates that are still shrinking (at least 3 months old)

- Tiling on heated screeds

In combination with ARDEX X 77 / X 78:

- Preparation of a special adhesive with high deformability and water-repellent properties

In combination with ARDEX N 23 W NEW:

- Production of a special adhesive with high deformability and water-repellent properties

ARDEX E 90 is a synthetic resin admix that can be used in combination with certain ARDEX tile adhesives to create a highly deformable adhesive bed. This significantly expands the range of applications for the tile adhesives (S2 adhesives).

Additional information

Handle with care during processing: avoid dust formation and release into the environment.

Dispose of the container and its contents in a solidified state in accordance with applicable local/regional/national/international regulations.

Technical data according to ARDEX quality standard

Product details

Labelling according to GHS/CLP	See relevant safety data sheet
Labelling according to ADR	See relevant safety data sheet
Packaging	Canister containing 4.5 kg net

ARDEX Baustoff GmbH
Hürmer Straße 40
A-3382 Loosdorf
AUSTRIA
+43 (0) 2754/7021-0
+43 (0) 2754/2490
office@ardex.at
www.ardex.at

Manufacturer with certified
QM/UM system according to
EN ISO 9001/14001



ARDEX E 90

Synthetic resin admix

Storage

Can be stored for approx. 12 months in dry, frost-free rooms in the original sealed container.
Seal opened containers tightly.
Store in an upright position.
