



ARDEX R 4 RAPID

Multi-purpose fast-curing putty

- Fast drying thanks to ARDURAPID-Plus effect
- Adheres to almost all substrates commonly used in construction without primer
- Extendable to zero
- Revision after 45 to 60 minutes



Area of application

For indoor and outdoor use, walls, floors and ceilings.

- Smoothing and filling of wall, ceiling and floor areas for wallpaper, paint coatings, dispersion plasters, wall and floor coverings on absorbent and non-absorbent substrates.
- Filling cracks, deep holes, slits and joints.
- For floors, for smoothing unevenness and trowel marks on gypsum and cement-based fillers.
- Outdoors, ARDEX R 4 RAPID may only be used on floor areas subject to low stress (e.g. repairs to areas subject to foot traffic only) and is not suitable for direct use or for receiving 2K coatings.
- For quick fixing of metal, joint and angle profiles.
- As a rapid construction system for quick repairs.

Art

Special cements, easily dispersible plastic powder and very fine-grained fillers.

When mixed with water, a stable levelling compound is formed which can be processed for approx. 15 minutes and hardens within 30 – 45 minutes through hydration and drying. On absorbent substrates, all coatings can be reworked after

approx.

45 minutes, and on non-absorbent substrates after approx. 60 minutes.

Preparation of the surface

ARDEX R 4 RAPID adheres practically insolubly to almost all substrates commonly found in construction. The substrate must be dry, solid, load-bearing, non-slip and free of release agents.

ARDEX Baustoff GmbH
Hürmer Straße 40
A-3382 Loosdorf
AUSTRIA
+43 (0) 2754/7021-0
+43 (0) 2754/2490
office@ardex.at
www.ardex.at

Manufacturer with certified
QM/UM system according to
EN ISO 9001/14001

Multi-purpose fast-curing putty

*the application recommendations listed apply only to indoor use.

Dispose of the container and its contents in a bound state in accordance with applicable local, regional, national and international regulations.

Page 2 of 3

ARDEX R 4 RAPID

Multi-purpose fast-curing putty

Product details

PH value approx.	11.5
Labelling according to GHS/CLP	See relevant safety data sheet
Labelling according to ADR	See relevant safety data sheet
EMICODE	EC 1 PLUS = very low emissions PLUS
GISCODE	ZP1 = cementitious product, low chromate content
Packaging	Bucket with 2.5 kg net
Storage	Can be stored in dry rooms for approx. 12 months in the original sealed container.
