



ARDEX SDB 15

Sound insulation sealing tape, self-adhesive

- Flexible and waterproof bridging
- Suitable for expansion joints, edge joints and connections prone to cracking



Area of application

Indoor and outdoor. Walls and floors.

For waterproofing and bridging expansion joints, edge joints, corners, connections prone to cracking and wall penetrations.

In the system with

- ARDEX S 1-K PLUS / S 1-K C PLUS Sealing compound
- ARDEX 8 + 9 Sealing compound
- ARDEX 8 + 9 L Sealing compound and sealing adhesive

Art

Stabilised butyl sealing tape with a release liner that is split in the middle and overlaps. The fleece allows good adhesion to construction chemicals.

Preparation of the surface

The substrate must be dry, solid, load-bearing and free of dust and release agents. The instructions in the ARDEX waterproofing compound brochures must be observed.

Processing

Wipe off half of the protective film from the ARDEX SDB 15 sound insulation sealing tape, then stick the self-adhesive sealing tape onto the horizontal surface and press down firmly. Next, wipe off the second half of the protective film and press firmly onto the vertical surface until an optimal bond with the substrate is achieved. Ensure that the sealing tapes overlap by approx. 5 cm.

To seal penetrations in the wall area, cut a piece of sealing tape to the appropriate size. Cut out the required opening depending on the diameter of the penetration and make a cross-cut. Then apply the sealing compound to the surface to be sealed. When applying the second coat of ARDEX sealing compounds, the sealing tapes are coated over the entire surface and thus integrated into the sealing layers.

Please note

ARDEX SDB 15 Sound insulation sealing tape must not come into direct contact with solvent-based waterproofing or adhesives.

If in doubt, carry out a test application or compatibility test.

When calculating the amount required, allow for an overlap of approx. 5 cm between the sealing tapes.

Note

The information in our safety data sheets must be observed.
For commercial use only!

Zusatzinformation

Handle with care during processing: avoid dust formation and release into the environment.

Dispose of the container and its contents in a sealed state in accordance with applicable local/regional/national/international regulations.



ARDEX SDB 15

Sound insulation sealing tape, self-adhesive

Technical data according to ARDEX quality standard

Thickness	0.9 mm
Width	150 mm
Roll length	20 m

Product details

Packaging	Box containing 1 roll, 20 m long
Storage	Can be stored in cool, dry rooms for approx. 24 months in the original sealed container.