



ARDEX SK 4 PROTECT

Cut protecting strip

- Cut-resistant tape made of polyamide and aramid fabric
- Self-adhesive
- Flexible and easy to process
- Alkali-resistant
- Very thin



Area of application

Indoor and outdoor. Walls and floors.

Cut-resistant tape made of polyamide and aramid fabric to protect the composite sealing during replacement or maintenance work in the area of elastic joints.

In the system with

- ARDEX S 1-K PLUS / S 1-K C PLUS Sealing compound
- ARDEX S7 PLUS Flexible slurry-type seal coating
- ARDEX 8+9/9 L Sealing compound
- ARDEX SK 100 W TRICOM Waterproofing membrane
- ARDEX SK TRICOM Sealing set

Art

Self-adhesive tape made of double-woven aramid fabric with reinforced hose, with cut-resistant effect for protecting composite seals during maintenance work in the area of elastic joints.

Preparation of the surface

Before applying ARDEX SK 4 PROTECT Cut protecting tape, the waterproofing must be completely dry. The substrate must be dust-free, solid and load-bearing.

Processing

ARDEX SK 4 PROTECT is bonded to the waterproofing after it has completely dried. To do this, remove the protective film on the back and stick the tape in the middle of the joint area. You can then start laying the tiles straight away.

Please note

ARDEX SK 4 PROTECT Cut Protection Tape must not be used in direct contact with solvent-based waterproofing or adhesives. In particularly exposed areas subject to aggressive chemical attack and exposure to oils, fuels or alcohols, seek technical advice before use. In case of doubt, carry out a trial application or compatibility test.

Note

The information in our safety data sheets must be observed.
For commercial use only!

Zusatzinformation

Handle with care during processing: avoid dust formation and release into the environment.
Dispose of the container and its contents in a sealed state in accordance with applicable local/regional/national/international regulations.

Technical data according to ARDEX quality standard

Base	Substrate: polyamide and aramid fabric; adhesive layer: hot melt adhesive; cover: release liner
Colour	Magenta / bright red
Thickness	0.65 mm
Width	40 mm

ARDEX Baustoff GmbH
Hürmer Straße 40
A-3382 Loosdorf
AUSTRIA
+43 (0) 2754/7021-0
+43 (0) 2754/2490
office@ardex.at
www.ardex.at

Manufacturer with certified
QM/UM system according to
EN ISO 9001/14001



ARDEX SK 4 PROTECT

Cut protecting strip

Width of the cut protection zone	40 mm
Cut resistance	Passed according to EN 388
Roll length	15 m
Processing temperature	-5 °C

Product details

Packaging	Roll, 4 cm wide and 15 m long; Pallet with 200 rolls
Storage	Can be stored in cool, dry rooms for approx. 12 months in the original sealed container.