



ARDEX STC VISCO T

Thickening agent

- Universally applicable
- Low consumption



Area of application

Indoor and outdoor. Wall.

ARDEX STC VISCO T is used to thicken ARDEX STC BINDER PU or ARDEX STC BINDER PU 2K for applications on vertical walls.

Special training is required for ARDEX stoneCARPET INDOOR applications (system partner).

Processing

For walls, mix ARDEX STC BINDER PU or ARDEX STC BINDER PU 2K with ARDEX STC VISCO T and prime the entire substrate with a roller or brush.

The mixing ratio for this is 1 kg of binder to 0.6 litres of ARDEX STC VISCO T.

Note

The information in our safety data sheets must be observed.
For commercial use only!

Zusatzinformation

Handle with care during processing: avoid dust formation and release into the environment.

Dispose of the container and its contents in a sealed state in accordance with applicable local/regional/national/international regulations.

Technical data according to ARDEX quality standard

Product details

Packaging	Container with 1.5 kg net
Storage	Can be stored in cool, dry rooms for approx. 24 months in the original sealed container.

Note on use: This data sheet is based on the current state of the art on the date of issue and has been compiled on the basis of our knowledge and experience. Despite conscientious processing information available, ARDEX Baustoff GmbH cannot accept any liability for the topicality and correctness accuracy of the information. The requirements of the respective building certification systems can be interpreted differently and depend on the respective product and place of use. The content does not constitute a legal relationship. In addition, the information in the technical and safety data sheets must be observed.

ARDEX Baustoff GmbH
Hürmer Straße 40
A-3382 Loosdorf
AUSTRIA
+43 (0) 2754/7021-0
+43 (0) 2754/2490
office@ardex.at
www.ardex.at

Manufacturer with certified
QM/UM system according to
EN ISO 9001/14001