

Technical data sheet

PANDOMO Clay Finish

Surface finish based on beeswax

- › Colour intensification and surface protection
- › Polishable
- › Ready to use
- › Breathable
- › Smear resistance
- › Not water-soluble after drying



Area of application:

Indoor.
Surface finish for protecting and intensifying the colour of
PANDOMO Clay wall surfaces.

Art:

Beeswax-based wax soap, ammonium tartrate, water; free from
oils

Processing:

PANDOMO Clay Finish is ready to use, undiluted, and applied in
a single coat using a non-abrasive Venetian smoothing trowel, a
small round brush or a cloth. We recommend smoothing with a
Venetian smoothing trowel. To increase the gloss level, the
surface can be treated with a white pad. Full protection is
achieved after 7 days.

Refinishing:

The PANDOMO Clay surface treated with PANDOMO Clay
Finish can be reworked after sanding with 80 grit sandpaper.

Technical data according to ARDEX quality standard

Material requirements	50–80 g/m ² depending on the condition of the substrate
-----------------------	--

Please note:

PANDOMO Clay Finish can also be lightly coloured with
PANDOMO CC colour concentrates (maximum addition 2%) to
achieve additional effects.

Due to the natural raw material base of PANDOMO Clay Finish,
milky soap deposits may occur. This can be largely avoided by
applying with a round brush. Containers and tools can be
cleaned with water immediately after use. PANDOMO Clay
Finish should be used at temperatures above +5°C.

If in doubt, test on a small area first.

Note:

The information in our safety data sheets must be observed.

For commercial users only!

Additional information:

Proceed carefully during application: avoid dust formation and
release into the environment.

Dispose of the container and its contents in a sealed state in
accordance with applicable local/regional/national/
international regulations.

open your space



Technical data sheet

PANDOMO Clay Finish

Surface finish based on beeswax

Product details

Labelling according to GHS/CLP	See relevant safety data sheet
Labelling according to ADR	See relevant safety data sheet
EMICODE	EC 1 PLUS = very low emissions PLUS
Packaging	Bucket with 1 kg net
Storage	Can be stored in dry rooms for at least 24 months in the original sealed container. Store in a frost-free place.
